

# TECHNICAL DATA: BS+

| Product Name                     | BS+<br>10    | BS+<br>16     | BS+<br>25    |
|----------------------------------|--------------|---------------|--------------|
| Nominal Performance              | 12 kW        | 16 kW         | 23 kW        |
| Minimum Performance              | 3 kW         | 5 kW          | 7 kW         |
| Nominal Efficiency               | 95,0%        | 95,0%         | 95,0%        |
| Minimum Efficiency               | 95,1%        | 94,3%         | 92,9%        |
| Power Consumption (Nominal)      | 39W          | 52W           | 66W          |
| Power Consumption (Minimum)      | 23W          | 25W           | 27W          |
| EN303-5:2012 Klasse              | 5            | 5             | 5            |
| Controller Version:              | V13          | V13           | V13          |
| Width (mm) (only boiler)         | 490          | 490           | 490          |
| Width including 280l hopper      | 980          | 980           | 980          |
| Width including 380l hopper      | 1240         | 1240          | 1240         |
| Boiler Depth (mm)                | 969          | 969           | 969          |
| Boiler Height (mm) *incl. Hopper | 1113 / *1220 | 1113 / *1220  | 1113 / *1220 |
| Chimney (mm)                     | 130          | 130           | 130          |
| Weight (kg)                      | 162          | 163           | 165          |
| Water capacity (liter)           | 36           | 36            | 36           |
| Ash can capacity (liter)         | 25           | 25            | 25           |
| Forward/Return/Filling           | ¾"           | ¾"            | ¾"           |
| Test # 300-ELAB-                 | 2052         | ADM. APPROVED | 2054         |

