

TECHNICAL DATA: RTB

Produkt Name	RTB 10	RTB 10 VAC	RTB 16	RTB 16 VAC	RTB 30	RTB 30 VAC	RTB 50	RTB 50 VAC	RTB 80
Nominal Performance	11 kW	11 kW	17 kW	17 kW	25 kW	25 kW	48 kW	48 kW	78kW
Minimum Performance	3 kW	3 kW	5,5 kW	5,5 kW	7,5 kW	7,5 kW	14 kW	14 kW	23 kW
Nominal Efficiency	93,9%	93,9%	91,1%	91,1%	91,4%	91,4%	93,6%	93,6%	93,6%
Minimum Efficiency	90,5%	90,5%	92,4%	92,4%	92,7%	92,7%	94,6%	94,6%	93,9%
Power Consumption (Nominal)	37W	37W	40W	40W	90W	90W	168W	168W	125W
Power Consumption (Minimum)	24W	24W	20W	20W	34W	34W	82W	82W	69W
EN303-5:2012 Klasse	5	5	5	5	5	5	5	5	5
Controller Version:	V13	V13	V13	V13	V13	V13	V13	V13	V13
Width (mm) (only boiler)	506	506	506	506	652	652	762	762	962
Depth (mm)	862	862	862	862	862	862	1114	1114	1296
Height (mm)	1055	1710 * 1982**	1055	1710* 1982**	1055	1710 * 1982**	1225	1880* 2152**	1518
Chimney (mm)	100	100	100	100	130	130	150	150	180
Weight (kg)	162	194	162	194	179	214	390	430	580
Water volume (liter)	36	36	36	36	48	48	78	78	105
Ash can (liter)	31	31	31	31	38	38	60	60	60
Forward/Return/Filling	¾"	¾"	¾"	¾"	¾"	¾"	1"	1"	5/4"
Test # 300-ELAB-	2042	2042	2045	2045	2064	2064	2179	2179	2216
* Boiler Height + Vacuum hopper									
**Boiler Height + Vacuum hopper + vacuum cyclone									

RTB 80

